SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ( ) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	18
	LAST NO. USED	18

MISSING SYMBOLS
NO MISSING SYMBOL NUMBER

DWG STATUS					ZONE	REVISION HISTORY	AUTH	DR	APVD 1	APVD 2
DATE	STG	REV	N/P	DIG						
30JL02	R	01	-	-		CLEARED REVISION COLUMN; ALL PARTS - REDRAWN TO P0 & UPDATED PDM ATTRIBUTES	226419	JVM	JVM	TTP
12SE03	R	02	-	-		REVISED GRAPHICS	241005	LOA	FKV	CD
17SE03	R	03	-	-		15326266 - UPDATED PDM ATTRIBUTES	245987	ADK	BG	TW
24OC03	R	04	-	-		UPDATED REVISION LEVEL IN CHART.	246088	LMB	LMB	RF
16AU04	R	05	-	-		ADDED TERMINAL I.D. NOTE; REMOVED "PXX" FROM GRAPHICS	258116	TSH	TSH	RF
16WY05	R	06	-	-		ALL PARTS - ADDED 3 COLUMNS TO CHART	268254	JS	JS	LN
05NO06	R	07	-	-		ALL PARTS - UPDATED PDM ATTRIBUTES	406683	RHO	JHP	RHO
16MR10	R	08	-	-		ALL PARTS - UPDATED PDM ATTRIBUTES	410248	FRE	FRE	VMR
04AU10	R	09	-	-		ALL PARTS - ADDED PLATING NOTE, UPDATED MAT'L CALLOUT AND ADDED CONTACT AREA & CRIMP AREA COLUMNS ON CHART	411497	JRL	JRL	VMR
30SE10	R	10	-	-		ALL PARTS - UPDATED PLATING NOTE	412114	AJP	JVM	VMR
23WY11	R	11	-	-		ALL PARTS - ADDED "PREFERRED MAT'L SIZE" COLUMN	414345	JAR	JAR	VMR





2 RIB SEAL POSITION REF
AND TERMINAL/CABLE ALIGNMENT
SCALE 5:1





3 RIB SEAL POSITION REF
SCALE 5:1

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. REFERENCE MATING COMPONENTS OR EQUIVALENT:

   TERMINAL - 15304706

3. * DENOTES DIMENSIONS MADE AT CUT-OFF AND CRIMP DIE.
4. DO NOT PROBE, TEST OR OTHERWISE CONTACT THE INTERIOR REGION (THE SPRING OR ANY MOVING PART) OF THIS TERMINAL. SEVERE DAMAGE CAN OCCUR, COMPROMISING THE PERFORMANCE OF THE ELECTRICAL INTERFACE.
5. PLATING TYPE:
   1. REFLOW TIN 1.9-3.3 MICROMETERS THICK WITH A COPPER UNDERPLATE 0.5 MICROMETER TO 1.0 MICROMETER THICK.

   PLATING TYPE INFORMATION SHOWN ABOVE IS REFERENCE ONLY. PLATING REQUIREMENTS ARE CONTAINED IN APPLICABLE MATERIAL SPECIFICATION.

PART NO	REV	N/P	STATUS	PREFERRED MAT'L SIZE	ALTERNATIVE MAT'L SIZE	MAT'L DESCRIPTION	SIZE (MM²)	ID	DIA	TYPE	$B_{1\pm0.2}$	APPLICATION	TYPICAL CABLE SEAL OR EQUIVALENT	TYPICAL SEALING CAVITY CONFIGURATION	CONTACT AREA PLATING TYPE (SEE NOTE 5)	CRIMP AREA PLATING TYPE (SEE NOTE 5)
15326267	04	A0	-	0.3 X 26.71	0.3 X 27.38	COPPER ALLOY	0.75 - 0.8	18	2.02 - 1.7	101	2.65	SEALED (MINI)	15305351	3.2 X 4 OVAL	1	1
15326266	04	A0	-	0.3 X 26.71	0.3 X 27.38	COPPER ALLOY	0.35 - 0.5	21	1.85 - 1.2	101	2.1	SEALED (MINI)	15365022	3.2 X 4 OVAL	1	1
15326265	04	A0	-	0.3 X 26.71	0.3 X 27.38	COPPER ALLOY	0.75 - 1	17	2.25 - 1.7	101	2.65	SEALED (GT)	15365060	Ø 4 ROUND	1	1
15326264	04	A0	-	0.3 X 26.71	0.3 X 27.38	COPPER ALLOY	0.35 - 0.5	21	1.85 - 1.2	101	2.1	SEALED (GT)	15366021	Ø 4 ROUND	1	1

DWG TYPE	PART DRAWING
STYLE	
VOLUME (CM³)	DISTR CODE D

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS IN ACCORDANCE WITH ASME Y14.5M-1994 (ASME/ANSI Y14.5M-1994) DIMENSIONS AND TOLERANCES ARE NONCUMULATIVE. SEPARATE PATTERNS OF FEATURES MAY BE SHOWN SEPARATELY PERPENDICULAR OF DATUM REFERENCES.

ALL DIMENSIONS ARE IN MILLIMETERS

REFERENCE

THIRD ANGLE PROJECTION

DO NOT SCALE
USE MATH DATA

NX

(2) PROCESS SENSITIVE DIMENSION

DIMENSIONS ENCLOSED IN ( ) INDICATE REFERENCE DIMENSIONS AND NO TOLERANCE UNITS ARE MILLIMETERS

DIMENSIONAL RANGE (MM)	CHART D
FROM 0	
TO 12	>12
TOLERANCE UNLESS OTHERWISE SPECIFIED	
±0.1	±0.2

ANGULAR TOLERANCE ±2°

DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE
WARREN, OH

		DATE
DR		
APVD1	H. CASTRILLON	18APR97
APVD2	FCO. KOPCA	21APR97
APVD3	S.C. HSIEH	30SE98
APVD4		
APVD5		

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI 10949001

MATERIAL: SEE CHART

DRAWING NAME: TAXI TERM F GT 150

DRAWING NUMBER: 12191815

SIZE	SCALE	FRAME NO	SHEET NO	STG	REV	N/P
A0	10:1	1 OF 1	2 OF	R	11	-