




ASSEMBLY INSTRUCTIONS GT 150 CONNECTION SYSTEM



REPRESENTATIVE WITH ANY QUESTIONS OR COMMENTS CONCERNING THESE ASSEMBLY INSTRUCTIONS. COMPONENT P/N'S AND REPAIR TOOL P/N'S ARE AVAILABLE FROM YOUR DELPHI SALES ENGINEER.










STEP 1: PLUG LEADS TO CONNECTOR ASSEMBLY PER PRINT.


STEP 2: AFTER ALL LEADS ARE BUILT, SEAT SIDE LOCK COVER (SLC). APPLY PRESSURE WITH FINGERS UNTIL SLC SLIDES INTO LOCK POSITION.

STEP 3: BUILD (1) ONE CONNECTOR POSITION ASSURANCE (CPA) TO CONNECTOR ASSEMBLY.


- A. HOLD CONNECTOR ASSEMBLY PLUGGING SIDE AWAY FROM HAND. HOLD CPA WITH EXTENSIONS TOWARD CONNECTOR.
- B. SLIDE EXTENSIONS INTO SLOTS AND SNAP INTO PLACE USING FINGERS.








STEP 2: AFTER ALL LEADS ARE BUILT, SEAT SIDE LOCK COVER (SLC). CUSTOMERS SHOULD CONTACT DELPHI'S ASSEMBLY TOOLING BUSINESS UNIT FOR THE SPECIFIC COMPONENT ASSEMBLY FIXTURE. THIS FIXTURE SEATS THE SLC TO ITS FINAL STAGE.









STEP 3: BUILD (1) ONE CONNECTOR POSITION ASSURANCE (CPA) TO CONNECTOR ASSEMBLY.

- A. HOLD CONNECTOR ASSEMBLY PLUGGING SIDE AWAY FROM HAND. HOLD CPA WITH EXTENSIONS TOWARD CONNECTOR.
- B. SLIDE EXTENSIONS INTO SLOTS AND SNAP INTO PLACE USING FINGERS.










STEP 1: PLUG LEADS TO CONNECTOR ASSEMBLY PER PRINT.


STEP 2: AFTER ALL LEADS ARE BUILT, SEAT SIDE LOCK

COVER (SLC). APPLY PRESSURE WITH FINGERS

UNTIL SLC SLIDES INTO LOCK POSITION.









STEP 2: AFTER ALL LEADS ARE BUILT, SEAT SIDE LOCK COVER (SLC). APPLY PRESSURE WITH FINGERS UNTIL SLC SLIDES INTO

LOCK POSITION.





FINAL ASSEMBLY INSTRUCTIONS FOR FEMALE & MALE GT 150 CONNECTOR ASSEMBLY



Delphi Connections Systems Page 9 of 9

10/31/00